



iDAQ-62934 4-slot USB 3.0 Industrial DAQ Chassis Module



Features

- USB 3.0 SuperSpeed
- Built-in USB hub
- Wide range power input
- LED status indicators
- Physical ID switch for multiple module identification
- 4 iDAQ slots
- 2 programmable function pin for timing signal (trigger, clock) input/output

Specifications

Analog Input

Please refer to the specifications of individual iDAQ analog input module

Analog Output

Please refer to the specifications of individual iDAQ analog input module

Digital Input

Please refer to the specifications of individual iDAQ analog input module

Digital Output

Please refer to the specifications of individual iDAQ analog input module

Counter

Please refer to the specifications of individual iDAQ analog input module

Programmable Function Pin

- **Channels** BNC x 2
- **Direction** Input or output, software configurable
- **Input level** Logic high: +3.5 V min.
Logic low: +1.5 V max.
- **Input protection voltage** +6.5 V max, -0.5 V min.
- **Pull-down resistor** 10 k Ω
- **Input signal frequency** 10 MHz max.
- **Response time** 20 ns max.
- **Debounce filter** 40 ns ~ 168 ms, software configurable
- **Output logic level** Logic high: +4.5 V min., 20 mA source max.
Logic low: +0.5 V max., 20 mA sink max.

USB Communication

- **Interface** SuperSpeed USB 3.0
- **Data transfer rate** 5 Gbps max.
- **USB upstream port** 1 port
- **USB downstream port** 1 port

Power Requirement

- **Power Input** 10~30 V_{DC}
- **Power Consumption** 24 W max., including modules and USB downstream port loads
- **Power consumption from USB** 100 μ A max.
- **Power connector** 2-pin spring terminal

Mechanical

- **Module dimensions** 178 x 100 x 71 mm (7.01 x 3.93 x 2.80 in.)
- **Weight** 680 g
- **Installation** DIN Rail/Wall Mount

Environment

- **Operating temperature** -20 °C to 60 °C (-4 °F to 140 °F)
- **Storage temperature** -40 °C to 70 °C (-40 °F to 158 °F)
- **Operating humidity** 10% to 90% RH, non-condensing
- **Storage humidity** 5% to 95% RH, non-condensing
- **Vibration** 5G_{rms}
- **Shock** 30G
- **Indoor use only**

Certification

- **EMC** CE, FCC
- **Safety** CB, UL

Ordering Information

- **IDAQ-62934** 4-slot USB 3.0 iDAQ Chassis Module